

CliniCool® Silver Series undercounter pharmacy/vaccine refrigerators are ideal for clinical labs, medical offices and pharmacies with a limited space and budget. These units offer superior temperature performance for safe storage of vaccines while meeting federal and state guidelines.



Standard Product Features:

- Cycle defrost
- Microprocessor temperature controller with battery back-up (batteries included)
- Adjustable operating temperature range: +36°F to +46°F (+2°C to +8°C)
- Digital temperature display
- Audible and visual high and low temperature alarms, with battery back up
- Remote alarm contacts
- 2 probes; 1 in air 1 in glycol bottle
- Four adjustable shelves (two large, two small) with guard rail on back to prevent product from being pushed against the back wall
- Bottom footed shelf to allow air circulation
- Back wall evaporator cover
- Forced draft circulation
- Keyed door lock
- LED light
- Magnetic door gasket for positive seal
- Leveling legs
- Probe access port (3/8")
- Powder coat exterior
- High density urethane foam cabinet and door insulation
- HFC-free refrigerant (R600a), foam insulation and packaging
- Pharmacy refrigerator/freezer toolkit and temperature logs
- Pyxis®, Omnicell® and AcuDose RX® compatible
- Cord label stating: Warning! Do not unplug the appliance or break circuit. Expensive vaccine in storage.
- Warranty: 2 years parts and labor, plus an additional 3 years for compressor parts only



Hydrocarbon refrigerant used in all CliniCool Undercounter models

Specifications and Ordering Information:

Model	LHP-2-UR-PH	LHP-2-URG-PH	LHP-3-UR-PH	LHP-3-URG-PH	LHP-3-URB-PH	LHP-5-UR-PH
Weight lbs	91	91	85	97	85	129
Overall Height in.	21 1/4*	21 1/4*	28 7/8*	28 7/8*	30 3/4*	32 1/8*
Overall Width in.	17 1/4*	17 1/4*	17 3/4*	17 3/4*	17 3/4*	23 3/4*
Overall Depth in.	19 1/4*	19 1/4*	19 1/2*	19 1/2*	22 3/4*	24*
Interior cu. ft.	1	1	2.5	2.5	2.5	5.2
Number of Shelves	2, adj	2 adj	4 adj	4 adj	4 adj	3 adj
Door Type	solid	glass	solid	glass	solid	solid
Defrost Type	cycle	cycle	cycle	cycle	cycle	cycle
Compressor Size	1/8 HP	1/8 HP	1/8 HP	1/8 HP	1/8 HP	1/6 HP
Plug (Receptacle)	5-15P	5-15P	5-15P	5-15P	5-15P	5-15P
Total Amp Draw	0.9	0.9	0.9	0.9	0.9	1.3
Voltage	115V, 60Hz	115V, 60Hz	115V, 60Hz	115V, 60Hz	115V, 60Hz	115V, 60Hz

Model	LHP-5-URG-PH	LHP-5-URB-PH	LHP-5-URBPH-ADA	LHP-5-URBG-PH	LHP-5-URBGPH-ADA	LHP-5-URBSS-PH
Weight lbs	129	137	150	150	150	135
Overall Height in.	32 1/8*	33 3/8*	31 15/16*	33 3/8*	31 15/16*	33 3/8*
Overall Width in.	23 3/4*	23 3/4*	23 3/4*	23 3/4*	23 3/4*	23 3/4*
Overall Depth in.	24*	24 1/2*	24 1/2*	25 1/2*	25 1/2*	24 1/2*
Interior cu. ft.	5.2	4.6	4.6	4.6	4.6	4.5
Number of Shelves	3 adj	2 adj, 1 fixed	2 adj, 1 fixed	2 adj, 1 fixed	2 adj, 1 fixed	2 adj, 1 fixed
Door Type	glass	solid	solid	glass	glass	Solid SS
Defrost Type	cycle	cycle	cycle	cycle	cycle	cycle
Compressor Size	1/6 HP	1/8 HP	1/8 HP	1/8 HP	1/8 HP	1/8 HP
Plug (Receptacle)	5-15P	5-15P	5-15P	5-15P	5-15P	5-15P
Total Amp Draw	1.3	1.74	1.74	1.74	1.74	1.74
Voltage	115V, 60Hz	115V, 60Hz	115V, 60Hz	115V, 60Hz	115V, 60Hz	115V, 60Hz

Exterior dimensions do not include 4" clearance required for installation.
Specifications subject to change without notice.



Receptacle Required



115V/1PH/ 60Hz
NEMA-5-15P



LABRepCo
An Employee-Owned Company