

CliniCool® Silver Series undercounter pharmacy/vaccine freezers are ideal for clinical labs, medical offices and pharmacies with a limited space and budget. These units offer superior temperature performance for safe storage of vaccines while meeting federal and state guidelines.

### Standard Product Features:

- Auto or Manual defrost
- Microprocessor temperature controller with battery back-up
- Adjustable operating temperature range: +36° F to +46° F
- Digital temperature display
- Audible and visual high and low temperature alarms, with battery back up
- Remote alarm contacts
- 2 probes; 1 in air and 1 in glycol bottle
- Adjustable or fixed shelves with guard rail on back to prevent product from being pushed against the back wall
- Bottom footed shelf to allow air circulation
- Back wall evaporator cover
- Forced draft circulation
- Keyed door lock
- LED light
- Magnetic door gasket for positive seal
- Leveling legs
- Probe access port (3/8")
- Powder coat exterior
- High density urethane foam cabinet and door insulation
- HFC-free refrigerant (R600a), foam insulation and packaging
- Pharmacy refrigerator/freezer toolkit and temperature logs
- Pyxis®, Omnicell® and AcuDose RX® compatible
- Cord label stating: Warning! Do not unplug the appliance or break circuit.



LHP-5-UFMBSS-PH

LHP-5-UFMB-PH



LHP-2-FM-PH

Expensive vaccine in storage.

- Warranty: 2 years parts and labor, plus an additional 3 years for compressor parts only



**Hydrocarbon refrigerant** used in all CliniCool Undercounter models

Specifications and Ordering Information:



LHP-5-UFMB-PH-ADA

Model	LHP-1-FA-PH	LHP-2-FM-PH	LHP-5-UFMB-PH	LHP-5-UFMBPH-ADA
Weight lbs	80	80	132	133
Overall Height in.	20 3/8*	20 3/8*	33 3/8*	31 15/16*
Overall Width in.	23 3/4*	23 3/4*	23 3/4*	23 3/4*
Overall Depth in.	24*	24*	24 1/2*	24 1/2*
Interior Height in.	12 3/8	13 7/8	24 1/12	24
Interior Width in.	17 3/4	17 3/4	19	19
Interior Depth in.	7 1/2	16	17 1/4	17 1/4
Interior cu. ft.	1	1.7	4.2	4.2
Temperature Range	+5°F to -13°F	+5°F to -13°F	+5°F to -13°F	+5°F to -13°F
# of Shelves	2, adj	2, adj	2, fixed	2, fixed
Door Type	solid	solid	solid	solid
Defrost Type	Control Auto	Manual	Manual	Manual
Compressor Size	1/8 HP	1/8 HP	1/8 HP	1/8 HP
Plug (Receptacle)	5-15P	5-15P	5-15P	5-15P
Total Amp Draw	1	1	1.5	1.5
Voltage	115V, 60Hz	115V, 60Hz	115V, 60Hz	115V, 60Hz



LHP-5-UFM-PH

Model	LHP-5-UFM-PH	LHP-5-UFM30-PH	LHP-5-UFM40-PH	LHP-5-UFMBSS-PH
Weight lbs	128	128	128	131
Overall Height in.	32 3/16*	32 1/8*	32 1/8*	33 3/8*
Overall Width in.	23 5/8*	23 3/4*	23 3/4*	23 3/4*
Overall Depth in.	24 1/4*	24*	24*	24 1/2*
Interior Height in.	26	24 7/8	26	24
Interior Width in.	19	17 5/8	19	19
Interior Depth in.	16	15 7/8	16	17 1/4
Interior cu. ft.	4	4	4	4.2
Temperature Range	+5°F to -13°F	-4°F to -22°F	-35°F to -45°F	+5°F to -13°F
# of Shelves	2, fixed	3 adj	3 adj	2, fixed
Door Type	solid	solid	solid	solid
Defrost Type	Manual	Manual	Manual	Manual
Compressor Size	1/8 HP	1/4 HP	1/4 HP	1/8 HP
Plug (Receptacle)	5-15P	5-15P	5-15P	5-15P
Total Amp Draw	1.4	2.2	2.2	1.5
Voltage	115V, 60Hz	115V, 60Hz	115V, 60Hz	115V, 60Hz

Please Note: All dimensions are nominal. All specifications subject to change without notice.



Receptacle Required



115V/1PH/ 60Hz  
NEMA-5-15P



**LABRepCo**  
An Employee-Owned Company