

Controlled Room Temperature (CRT) Cabinets are designed specifically for medical applications requiring precise temperature management for medications stored at room temperature (68°F to 77°F). These CRT units feature a digital microprocessor temperature controller and a forced air directional refrigeration system to ensure temperature uniformity at all times.



LHP-11-CRTHG

LHP-1-CRT

Standard Product Features:

- Cycle defrost
- Microprocessor temperature controller
- Digital temperature display
- Audible and visual high and low temperature alarms
- Remote alarm contacts
- Adjustable operating temperature range:
+68°F to +77°F (+20°C to +25°C)
- 3 adjustable shelves
- Forced draft circulation
- Keyed door lock
- Heavy duty door handle
- Magnetic door gasket for positive seal
- 3" Swivel Casters (Only Models 12 cu. ft & up)
- LED Interior light
- Probe access port (3/8")
- 2 probes; 1 in air and 1 in sample bottle
- Vaccine storage power cord warning label
- Powder coat exterior
- High density urethane foam cabinet insulation
- Pyxis®, Omnicell® and AcuDose RX® compatible
- Hydrocarbon, natural refrigerant (R290)
- UL/C-UL Listed
- Warranty: 1 year parts and labor warranty, plus an additional 4 year compressor parts warranty



Hydrocarbon refrigerant used in
all CRT models

Specifications and Ordering Information:



LHP-3-CRT



LHP-5-CRTG

Models	LHP-1-CRT	LHP-1-CRTG	LHP-3-CRT	LHP-3-CRTG	LHP-5-CRTG
Shipping Weight (lbs.)	91	91	85	97	129
Exterior Dimensions (in.) W x D x H	17 1/4" x 19 1/4" x 21 1/4"	17 1/4" x 19 1/4" x 21 1/4"	17 3/4" x 19 1/4" x 28 1/8"	17 3/4" x 19 1/2" x 28 7/8"	23 3/4" x 24" x 32 1/8"
Interior Dimensions (in.) W x D x H	14" x 8 7/8" x 15 3/4"	14" x 8 7/8" x 15 3/4"	14 1/4" x 13 1/4" x 23 1/4"	14 1/4" x 13 1/4" x 23 1/4"	19 1/4" x 17 1/4" x 24 1/2"
Interior Cu. Ft.	1	1	2.5	2.5	5.2
Number of Shelves	2 adj	2 adj	4 adj	4 adj	3 adj
Defrost Type	Cycle	Cycle	Cycle	Cycle	Cycle
Refrigerant	R600a	R600a	R600a	R600a	R600a
Compressor Size HP	1/8	1/8	1/8	1/8	1/6
Plug (receptacle)	5-15R	5-15R	5-15R	5-15R	5-15R
Total Amp Draw	.90	.90	.90	.90	1.3
Voltage	115V, 1/8HP, 60Hz	115V, 1/8HP, 60Hz	115V, 1/8HP, 60Hz	115V, 1/8HP, 60Hz	115V, 1/6HP, 60Hz

Specifications subject to change without notice.



LHP-16-CRTHG



LHP-36-CRTHG

Models	LHP-3-CRTB	LHP-5-CRTB	LHP-5-CRTBG
Shipping Weight (lbs.)	85	137	150
Exterior Dimensions (in.) W x D x H	17 3/4" x 22 3/4" x 30 3/4"	23 3/4" x 24 1/2" x 33 3/8"	23 3/4" x 25 1/2" x 33 3/8"
Interior Dimensions (in.) W x D x H	14" x 13 1/4" x 23 1/4"	19 1/4" x 17 1/4" x 24 1/2"	19 1/4" x 17 1/4" x 24 1/2"
Interior Cu. Ft.	2.5	4.6	4.6
Number of Shelves	4 adj	2 adj & 1 fixed	2 adj & 1 fixed
Defrost Type	Cycle	Cycle	Cycle
Refrigerant	R600a	R600a	R600a
Compressor Size HP	1/8	1/8	1/8
Plug (receptacle)	5-15R	5-15R	5-15R
Total Amp Draw	.90	1.74	1.74
Voltage	115V, 1/8HP, 60Hz	115V, 1/8HP, 60Hz	115V, 1/8HP, 60Hz

Specifications subject to change without notice.

Receptacle Required
115V/1PH/ 60Hz
NEMA-5-15R



LABRepCo
An Employee-Owned Company

Specifications and Ordering Information:

Models	LHP-11-CRTHG	LHP-12-CRTHG	LHP-16-CRTHG	LHP-23-CRTHG	LHP-26-CRTHG	LHP-36-CRTHG	LHP-49-CRTHG
Shipping Weight (lbs.)	209	258	275	336	315	355	538
Exterior Dimensions (in.) W x D x H	23 3/4" x 26 1/2" x 59"	25" x 29 3/4" x 65 3/4"	25" x 29 3/4" x 79"	26 7/8" x 34 3/4" x 81 3/4"	28 3/8" x 36 1/2" x 84 3/4"	39 5/8" x 34 3/4" x 79 3/4"	54" x 34 3/4" x 81 3/4"
Interior Dimensions (in.) W x D x H	19 7/8" x 18 3/8" x 53 1/2"	19 3/4" x 19 1/4" x 36 1/4"	20" x 19 1/2"D x 49 1/4"	22" x 25 1/4" x 52 1/2"	23 3/4" x 28" x 52 1/2"	34 7/8" x 23 5/8" x 52 3/4"	49" x 24 5/8" x 52 1/2"
Interior Cu. Ft.	10.5	12	16	23	26	36	49
Number of Shelves	6 adj	3 adj	3 adj	4 adj	4 adj	8 adj	8 adj
Defrost Type	Cycle	Cycle	Cycle	Cycle	Cycle	Cycle	Cycle
Refrigerant	R290a	R290a	R290a	R290a	R290a	R134a	R290a
Compressor Size HP	1/3	1/5	1/5	3/8	1/5	1/2	1/2
Plug (receptacle)	5-15R	5-15R	5-15R	5-15R	5-15R	5-15R	5-15R
Total Amp Draw	2.3	3	3	6	3	9	7
Voltage	115V, 1/3HP, 60Hz	115V, 1/5HP, 60Hz	115V, 1/5HP, 60Hz	115V, 3/8HP, 60Hz	115V, 1/5HP, 60Hz	115V, 1/2HP, 60Hz	115V, 1/2HP, 60Hz

Specifications subject to change without notice.

Models	LHP-11-CRTSD	LHP-12-CRTSD	LHP-16-CRTSD	LHP-23-CRTSD	LHP-26-CRTSD	LHP-36-CRTSD	LHP-49-CRTSD
Shipping Weight (lbs.)	183	227	237	250	235	310	446
Exterior Dimensions (in.) W x D x H	23 3/4" x 26 1/2" x 59"	25" x 29 3/4" x 65 3/4"	25" x 29 3/4" x 79"	26 7/8" x 34 3/4" x 81 3/4"	28 3/8" x 36 1/2" x 84 3/4"	39 5/8" x 34 3/4" x 81 3/4"	54" x 34 3/4" x 81 3/4"
Interior Dimensions (in.) W x D x H	19 7/8" x 18 3/8" x 53 1/2"	19 3/4" x 19 1/4" x 36 1/4"	20" x 19 1/2"D x 49 1/4"	22" x 25 1/4" x 52 1/2"	23 3/4" x 28" x 52 1/2"	37 7/8" x 23 5/8" x 52 3/4"	49" x 24 5/8" x 52 1/2"
Interior Cu. Ft.	10.5	12	16	23	26	36	36
Number of Shelves	6 adj	3 adj	3 adj	4 adj	4 adj	8 adj	8 adj
Defrost Type	Cycle	Cycle	Cycle	Cycle	Cycle	Cycle	Cycle
Refrigerant	R290a	R290a	R290a	R290a	R290a	R134a	R290a
Compressor Size HP	1/3	3/8	3/8	3/8	1/5	1/2	1/2
Plug (receptacle)	5-15R	5-15R	5-15R	5-15R	5-15R	5-15R	5-15R
Total Amp Draw	2.3	6	6	6	3	9	7
Voltage	115V, 1/3HP, 60Hz	115V, 3/8HP, 60Hz	115V, 3/8HP, 60Hz	115V, 3/8HP, 60Hz	115V, 1/5HP, 60Hz	115V, 1/2HP, 60Hz	115V, 1/2HP, 60Hz

Specifications subject to change without notice.

Receptacle Required
115V/1PH/ 60Hz
NEMA-5-15R

